



Front ITO Film-0.188mm

Back ITO Glass-1.8mm

Thick: 2.3±0.15

- Notes:
- 1.Type:Film to Glass
  - 2.Operating Voltage:≤10v
  - 3.Operation Temperature:-20°C~65°C  
Storage Temperature:-30°C~70°C
  - 4.Life Time:1,000,000 times
  - 5.Connect Material:FPC
  - 6.Response Time:≤10ms
  - 7.Linearity:≤1.5%
  - 8.Transmittance:≥75%
  - 9.Surface Hardness≥3H(pencil)
  - 10.Operation force:60g~150g

- 11.Resistance:50Ω < PIN1,PIN2 < 250Ω  
50Ω < PIN2,PIN4 < 250Ω  
50Ω < PIN4,PIN5 < 250Ω  
50Ω < PIN5,PIN1 < 250Ω

TOLERANCES  
(UNLESS OTHERWISE STATED)  
DECIMALS ANGLES ±0.5%

|                 |         |
|-----------------|---------|
| >2000MM         | ±2.00MM |
| 1600< X ≤2000MM | ±1.20MM |
| 1200< X ≤1600MM | ±0.80MM |
| 800< X ≤1200MM  | ±0.50MM |
| 400< X ≤800MM   | ±0.40MM |
| 120< X ≤400MM   | ±0.30MM |
| 30< X ≤120MM    | ±0.20MM |
| <30MM           | ±0.10MM |

**GreenTouch** GreenTouch Technology Co.,Ltd

|            |              |      |          |         |     |
|------------|--------------|------|----------|---------|-----|
| Model No.: | GT-5W-104A-1 | Size | 10.4"    | Ratio   | 4:3 |
| Structure  | G+F          | Unit | mm       | Scale   | 1:1 |
| Design     | 李俊           | Date | 2015,8,5 | Page    | 1/1 |
| Check      | 付作书          | Date | 2015,8,5 | Version | A0  |
| Release    | 汪燕           | Date | 2015,8,5 |         |     |