



Front ITO Film-0.188mm  
Back ITO Glass-1.8mm  
Thick: 2.3 ± 0.15

- Notes:
- 1.Type:Film to Glass
  - 2.Operating Voltage:≤10V
  - 3.Operating Temperature:-20°C~65°C
  - 4.Life Time:1,000,000 times
  - 5.Connect Material:FPC
  - 6.Response Time:≤10ms
  - 7.Linearity:≤1.5%
  - 8.Transmittance:≥75%
  - 9.Surface Hardness:≥3H(pencil)
  - 10.Operation force:60g~150g

11. Resistance:50Ω < PIN1, PIN2 < 250Ω  
50Ω < PIN2, PIN4 < 250Ω  
50Ω < PIN4, PIN5 < 250Ω  
50Ω < PIN5, PIN1 < 250Ω

TOLERANCES  
(UNLESS OTHERWISE STATED)

DECIMALS	ANGLES	±0.5%
>2000MM	±2.00MM	
1600 < X ≤ 2000MM	±1.20MM	
1200 < X ≤ 1600MM	±0.80MM	
800 < X ≤ 1200MM	±0.50MM	
400 < X ≤ 800MM	±0.40MM	
120 < X ≤ 400MM	±0.30MM	
30 < X ≤ 120MM	±0.20MM	
< 30MM	±0.10MM	

		GreenTouch Technology Co., Ltd	
		Model No.:	GT-SW-15A-1
Structure	G+F	Unit	mm
Design	李俊	Date	2015.8.5
Check	付作书	Date	2015.8.5
Release	汪陈	Date	2015.8.5
Ratio	4:3	Scale	1:1
Page	1/1	Version	A0