



Front ITO Film-0.188mm  
Back ITO Glass-1.8mm

Thick: 2.3±0.15

- Notes:
- 1.Type:Film to Glass
  - 2.Operating Voltage:≤10v
  - 3.Operation Temperature:-20℃~65℃  
Storage Temperature:-30℃~70℃
  - 4.Life Time:1,000,000 times
  - 5.Connect Material:FPC
  - 6.Response Time:≤10ms
  - 7.Linearity:≤1.5%
  - 8.Transmittance:≥75%
  - 9.Surface Hardness≥3H(pencil)
  - 10.Operation force:60g~150g

- 11.Resistance:50Ω < PIN1,PIN2 < 250Ω  
50Ω < PIN2,PIN4 < 250Ω  
50Ω < PIN4,PIN5 < 250Ω  
50Ω < PIN5,PIN1 < 250Ω

TOLERANCES  
(UNLESS OTHERWISE STATED)  
DECIMALS ANGLES ±0.5%

>2000MM	±2.00MM
1600< X ≤2000MM	±1.20MM
1200< X ≤1600MM	±0.80MM
800< X ≤1200MM	±0.50MM
400< X ≤800MM	±0.40MM
120< X ≤400MM	±0.30MM
30< X ≤120MM	±0.20MM
<30MM	±0.10MM



GreenTouch Technology Co.,Ltd

Model No.:	GT-5W-17.0B-1	Size	17"	Ratio	4:3
Structure	G+F	Unit	mm	Scale	1:1
Design	李俊	Date	2015,8,5	Page	1/1
Check	付作书	Date	2015,8,5	Version	A0
Release	汪燕	Date	2015,8,5		