



Front ITO Film-0.188mm

Back ITO Glass-1.8mm

- Notes:
- Type: Film to Glass
  - Operating Voltage: ≤10v
  - Operation Temperature: -20°C ~ 65°C  
Storage Temperature: -30°C ~ 70°C
  - Life Time: 1,000,000 times
  - Connect Material: FPC
  - Response Time: ≤10ms
  - Linearity: ≤1.5%
  - Transmittance: ≥75%
  - Surface Hardness: ≥3H (pencil)
  - Operation force: 60g ~ 150g

11. Resistance: 50Ω < PIN1, PIN2 < 250Ω  
50Ω < PIN2, PIN4 < 250Ω  
50Ω < PIN4, PIN5 < 250Ω  
50Ω < PIN5, PIN1 < 250Ω

TOLERANCES  
(UNLESS OTHERWISE STATED)  
DECIMALS ANGLES ±0.5%

>2000MM	±2.00MM
1600 < X ≤ 2000MM	±1.20MM
1200 < X ≤ 1600MM	±0.80MM
800 < X ≤ 1200MM	±0.50MM
400 < X ≤ 800MM	±0.40MM
120 < X ≤ 400MM	±0.30MM
30 < X ≤ 120MM	±0.20MM
< 30MM	±0.10MM

**格林触控**  
**GreenTouch** GreenTouch Technology Co., Ltd

Model No.:	GT-5W-19D-1	Size	19"	Ratio	4:3
Structure	G+F	Unit	mm	Scale	1:1
Design	李俊	Date	2016.5.16	Page	1/1
Check	付作伟	Date	2016.5.16	Version	A0
Release	汪燕	Date	2016.5.16		